Aluminum Adjustable Height Gantry Crane with Glass Filled Nylon Casters 10 Ft. Wide x 12 Ft. Max Usable Height 2,000 Lb. Capacity Silver

MODEL AHA-2-10-12

Overhead Lifting / Adjustable Height Aluminum Gantry Cranes

PRODUCT OVERVIEW

The adjustable height Aluminum Gantry crane combines lightweight and rigid, sturdy construction into one unit. The all aluminum construction of this gantry crane makes it corrosion resistant and perfect for outdoor use. The lightweight I-beam allows for simple height adjustments. All pinned connections make it possible for single person set up and take down in just minutes. Included are two (2) straps, allowing one person to transport the gantry crane in one neat package.

KEY FEATURES

- Heavy-duty welded aluminum construction for long lasting use
- Each unit includes four swivel glass filled nylon casters with four-way position locks for safe positioning
- Easy adjustable height can be done with fork truck or other overhead lifting device
- All units comply with applicable CMAA and ANSI specifications

CORE PRODUCT DATA

ASSEMBLED WEIGHT	ASSEMBLED SIZE	SHIP WEIGHT
213 lbs	53.75" W x 120" L x 150" H	261 lbs
PACKAGE 1 SIZE	**COLOR / FINISH**	**FREIGHT TYPE**
29" W x 144" D x 20" H	Silver	LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,000
Overall I-Beam Length (ft.)	10
I-Beam Height (In.)	6
I-Beam Flange Width (in.)	3-5/16
Under I-Beam Range (in.)	114 to 144
Base Width (in.)	53-3/4
Caster Quantity/Diameter/Width (in.)	(4) 8 x 2
Caster Type	Swivel (4) Position Locking Casters
Caster Material	Glass-Filled Nylon
Caster Top Plate (in.)	4 x 4 1/2
Usable Trolley Travel Distance (in.)	96-1/4
Increment Height Adjustment (in.)	6

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?PID=522