# Steel Lift and Side Link Tilt Scissor Table 36 In. x 54 In. 4000 Lb. Capacity Blue

**MODEL EHLTTS-3654-4-48**

Ergonomic Solutions / Lift & Tilt Scissor Tables

## PRODUCT OVERVIEW

The lift and tilt scissor lift performs both lifting and tilting operations. There is a restraining chain and lip to keep the load in place during tilting. Safety features include an electric toe guard to protect workers from pinch points during lowering of the table, velocity fuses to hold platform position in the event of a hose or fitting failure, four (4) push-button hand pendent control, upper limit switch to stop travel at maximum height and reduce motor wear, and maintenance prop. The end tilt is standard with a side tilt available. There is optional accordion skirting available for both the lifting and tilting portions of the table.

## KEY FEATURES

- Lift & tilt scissor lift includes a restraining chain and lip to keep load in place
- Features an electric toe guard to protect workers during lowering
- Velocity fuses hold platform position in the case of a hose or fitting failure
- Hand pendant control includes a switch to stop travel at maximum height

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 1165 lbs | 38.25" W x 54" L x 23.8125" H | 1500 lbs |
| **PACKAGE 1 SIZE** | **COLOR / FINISH** | **FREIGHT TYPE** |
| 38" W x 54" D x 16" H | Blue | LTL Palletized |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 4,000 |
| **Platform Lowered Height (in.)** | 12 |
| **Platform Raised Height (in.)** | 48 |
| **Platform Width (in.)** | 36-1/4 |
| **Platform Length (in.)** | 54 |
| **Deck Lip Height (in.)** | 12 |
| **Coil Cord Length (in.)** | 96 |
| **End Tilt (degrees)** | 45 |
| **Overall Width (in.)** | 38-1/4 |
| **Overall Length (in.)** | 54 |
| **Maximum Height (in.)** | 76-9/16 |
| **Safety Stop Lift Deck Toe Guard Meets OSHA** | 1910.212 |
| **Motor Voltage** | 460 |
| **Motor Phase** | 3 |
| **Control** | Handheld |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=209