# Steel Portable Foot Pump Hefti-Lift 51 In. x 79-3/8 In. 1500 Lb. Capacity Blue

**MODEL HYD-15**

Ergonomic Solutions / Hefti-Lifts

## PRODUCT OVERVIEW

The Hefti-Lift is a user friendly, portable hydraulic lift. The lift provides reliable, power lifting when moving and positioning loads. The non-slip chain is used for accurate positioning while the unit rolls easily on two rigid and two swivel poly-on-steel casters that includes a foot operated brake. The lift is all welded construction with a chrome platform and uprights. Not for use with pallets.

## KEY FEATURES

- Non-slip chain provides accurate deck positioning
- Two rigid and two swivel poly-on-steel casters roll smoothly either loaded or unloaded
- Removable platform allows operation requiring forks
- Welded steel construction provides long lasting rugged use

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 420 lbs | 29" W x 51" L x 79.375" H | 479 lbs |

| PACKAGE 1 SIZE | COLOR / FINISH | FREIGHT TYPE |
|---|---|---|
| 40" W x 64" D x 85" H | Blue | LTL Palletized |

**AVAILABILITY** Out of Stock - Please Contact Sales **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 1,500 |
| **Platform Width/Length (in.)** | 23 x 31-1/2 |
| **Service Range (in.)** | 4 to 63 |
| **Operation** | Foot Pump |
| **Platform Travel per Stroke (in.)** | 3/4 |
| **Individual Fork Width/Length (in.)** | 5-9/16 x 31-1/2 |
| **Fork Spacing (in.)** | 22-7/8 |
| **Handle Height (in.)** | 42 |
| **Back Caster Quantity/Diameter/Width (in.)** | (2) 6 x 2 |
| **Back Caster Type** | Swivel |
| **Front Caster Quantity/Diameter/Width (in.)** | (2) 3 x 2 |
| **Front Caster Type** | Rigid |
| **Caster Material** | Poly-on-Steel |
| **Outrigger Inside Dimension (in.)** | 11-3/4 |
| **Outrigger Outside Dimension (in.)** | 2-7/8 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?PID=261