# Steel Orbit Non Telescoping Lift Boom 24 In. Fork Pocket Center 4,000 Lb. Capacity Blue

**MODEL LM-OBNT-4-24**

Fork Truck Attachments / Orbiting Fork Truck Booms

## PRODUCT OVERVIEW

The non-telescoping orbit lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a locking detest and safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

## KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 337 lbs | 32" W x 80.875" L x 26.625" H | 337 lbs |

| PACKAGE 1 SIZE | COLOR / FINISH | FREIGHT TYPE |
|---|---|---|
| 32" W x 83" D x 27" H | Blue | LTL Loose |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 4,000 |
| **Fork Pocket Center (in.)** | 24 |
| **Fork Pocket Size (in.)** | 7-1/2 x 2-1/2 |
| **Restraint Length (in.)** | 36 |
| **Boom Style** | Non-Telescoping |
| **Minimum/Maximum Hook Point (in.)** | 36/78 |
| **Single-Hook Capacity at 36" (lb.)** | 4,000 |
| **Single-Hook Capacity at 48" (lb.)** | 3,750 |
| **Single-Hook Capacity at 60" (lb.)** | 3,500 |
| **Single-Hook Capacity at 72" (lb.)** | 3,250 |
| **Single-Hook Capacity at 78" (lb.)** | 3,000 |
| **Overall Max Tilted Height (in.)** | 57-3/16 |
| **Retracted Hook Height (in.)** | 5-1/2 |
| **Max Tilted Hook Height (in.)** | 38-1/4 |
| **Maximum Tilt Degree** | 37 |
| **Boom Type** | Orbit Boom |
| **OSHA** | 1910.178(a)(4) |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=1775