

# Steel Pallet Master/Server Stacker 12 Volt DC Powered 60 In. Raised Height 4,000 Lb. Capacity Blue

**MODEL PMPS-60-DC**

Ergonomic Solutions / Pallet Master/Servers

## PRODUCT OVERVIEW

The pallet master/server enables one person to easily move fully loaded pallets without the use of a fork truck. The unique straddle design works well with pallets and skids with and without an understructure. The unit is ideal for loading and unloading semi-trailers. Hand pendant control on an eight (8) foot coil cord standard. Floor lock standard. All welded steel construction.

## KEY FEATURES

- Easily move fully loaded pallets enabled by one person
- Straddle design works pallets and skids with or without an understructure
- Ideal for loading and unloading semi-trailers without strenuous work
- Hand pendant control on an eight (8) foot coil cord standard



## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**1029 lbs**

**ASSEMBLED SIZE**  
**58" W x 66" L x 87" H**

**SHIP WEIGHT**  
**1060 lbs**

**PACKAGE 1 SIZE**  
**64" W x 64" D x 94" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                                  |                                       |
|--------------------------------------------------|---------------------------------------|
| Uniform Capacity (lb.)                           | 4,000                                 |
| Operation                                        | (1) 12V DC                            |
| Fork Width/Length (in.)                          | 4 x 36                                |
| Service Range (in.)                              | 3 to 60                               |
| Adjustable Fork Spacing (in.)                    | 8 to 37                               |
| Leg Spacing (in.)                                | 49-1/2                                |
| Handle Height (in.)                              | 36                                    |
| Coil Cord Length (in.)                           | 96                                    |
| Rear Swivel Caster Quantity/Diameter/Width (in.) | (2) 8 x 3                             |
| Rear Caster Material                             | Phenolic                              |
| Front Wheel Quantity/Diameter/Width (in.)        | (2) 8 x 2                             |
| Front Wheel Material                             | Glass Filled Nylon                    |
| Overall Width (in.)                              | 58                                    |
| Overall Length (in.)                             | 66                                    |
| Overall Raised Height (in.)                      | 101                                   |
| Overall Lowered Height (in.)                     | 87                                    |
| Maximum Fork Height Before Carriage Exceeds 1    | 42                                    |
| Steel Construction                               | ASTM A-36 Minimum                     |
| Battery Depth                                    | 11                                    |
| Battery Width                                    | 7                                     |
| Battery Height                                   | 9                                     |
| Battery Weight                                   | 42                                    |
| Battery Freight Class                            | 70                                    |
| Battery NMFC Number                              | 60680                                 |
| Battery NMFC Description                         | UN2794 BATTERIES WET FILLED WITH ACID |
| Battery Subclass                                 | 1                                     |
| Lithium Battery Configuration                    | C -- Contained In                     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=243>