

# Steel Narrow Mast Stacker DC Powered 62 In. Raised Height Fixed Fork 27 In. Fork Width 1,500 Lb. Capacity Black / Yellow

**MODEL SNM15-62-FF-27**

Ergonomic Solutions / Narrow Mast Stackers with Powered Drive and Powered Lift



## PRODUCT OVERVIEW

The narrow mast stacker is great for the shipping and manufacturing facilities. The stacker provides a fast efficient solution to loading and unloading products in closely confined areas. The stacker features a simple throttle design for lifting control, as well as, infinite forward and reverse speed adjustments. The unit drives on poly on steel steering and load wheels, which provide excellent maneuverability. A battery charger, gauge and horn are included. Models are available with fixed or adjustable forks as well as fixed or adjustable leg supports.

## KEY FEATURES

- Emergency reverse belly switch instantly reverses direction
- Stacker is an efficient solution to loading and unloading in closely confined areas
- Throttle design lifts and controls speed adjustments for ideal operation and optimal results
- Includes poly-on-steel wheels for excellent maneuverability and fixed forks for maximum efficiency

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**768 lbs**

**ASSEMBLED SIZE**  
**77.25" W x 66" L x 28" H**

**SHIP WEIGHT**  
**772 lbs**

**PACKAGE 1 SIZE**  
**60" W x 75" D x 84" H**

**COLOR / FINISH**  
**Black / Yellow**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Temporarily Unavailable - Please Contact Sales  
Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: YES**

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                             |                       |
|---------------------------------------------|-----------------------|
| Uniform Capacity (lb.)                      | 1,500                 |
| Service Range (in.)                         | 2 to 62               |
| Fork Width/Length (in.)                     | 5-9/10 x 42-1/8       |
| Fixed Fork Spacing (in.)                    | 26-3/4                |
| Overall Mast Height (in.)                   | 78                    |
| Drive Motor                                 | DC 24V / 0.4 KW       |
| Lift Motor                                  | DC 24V / 2.0 KW       |
| Battery                                     | (2) 12V / 80 Ah       |
| Battery Charger                             | 24V / 8 amp           |
| Operation Time with Constant Use (hrs.)     | 3 to 4                |
| Operation Time with Intermittent Use (hrs.) | 8                     |
| Turning Radius (in.)                        | 88-5/8                |
| Travel Speed - Loaded (MPH)                 | 1.24                  |
| Travel Speed - Unloaded (MPH)               | 1.86                  |
| Battery Depth                               | 8                     |
| Battery Width                               | 14                    |
| Battery Height                              | 7                     |
| Battery Weight                              | 56                    |
| Battery Freight Class                       | 60                    |
| Battery NMFC Number                         | 60700                 |
| Battery NMFC Description                    | Gel batteries on unit |
| Lithium Battery Configuration               | C -- Contained In     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA