# Steel Truck Dock Board 72 In. x 72 In. 25,000 Lb. Capacity Blue

**MODEL TS-25-7272**

Loading Dock Equipment / Steel Truck Dockboards

## PRODUCT OVERVIEW

The steel truck dock board is constructed of high strength (55,000 psi) steel for long life. Deck is diamond plated for safe, efficient use. Locking legs minimize ramp movement and are uneven to allow the dock board to sit canted for easier floor pickup by fork trucks when not in use. Standard with lever lift for quick portability with fork truck. Legs are located 12" from the edge of the dock board. Manufactured in compliance with OSHA. Optional accessories: lifting chains, span locks, span pins/holes and removable pickup loops.

## KEY FEATURES

- Manufactured from high-strength steel tread plate for maximum durability
- Heavy-duty steel curbs are welded in place for maximum strength
- Includes patented lever lift for easy fork truck positioning
- Smooth transition provided by beveled entrance and exit

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 821 lbs | 75.0625" W x 71.8125" L x 19.8125" H | 859 lbs |

| PACKAGE 1 SIZE | COLOR / FINISH | FREIGHT TYPE |
|---|---|---|
| 76" W x 73" D x 19" H | Blue | LTL Loose |

**AVAILABILITY** Available

**QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 25000 |
| **Height Difference at 11 degree/19 percent (in.)** | 12 |
| **Steel Strength (psi)** | 55000 |
| **Bend Degree** | 11 |
| **Bend Distance from Beveled Edge (in.)** | 9 |
| **Leg Distance from Edge (in.)** | 12 |
| **Deck Thickness (in.)** | 1/2 |
| **OSHA** | 1910.30(a) |
| **ANSI** | MH 30.2 |
| **Usable Width (in.)** | 67-3/4 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=37