

# Galvanized Steel DC Powered Jib Crane 3-5 Ft. Boom 2,000 Lb. Capacity Gray

**MODEL WTJ-20-3-DC-GAL**

Overhead Lifting / Power Lift Jib Cranes

## PRODUCT OVERVIEW

The Jib crane is ideal for lifting objects in a variety of areas. With a steel construction and a galvanized finish, the jib crane also features a telescopic boom with an adjustable length and height, manual boom rotation, powered cable winch for easy lifting and maneuvering, and a plug in handheld winch control. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

## KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**243 lbs**

**ASSEMBLED SIZE**  
**13.5" W x 51.8125" L x 68.8125" H**

**SHIP WEIGHT**  
**265 lbs**

**PACKAGE 1 SIZE**  
**30" W x 67" D x 18" H**

**COLOR / FINISH**  
**Gray**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                              |                   |
|----------------------------------------------|-------------------|
| Uniform Capacity (lb.)                       | 2,000             |
| Boom Reach (in.)                             | 39-1/4 to 63-1/4  |
| Boom Height (in.)                            | 59-9/16 to 96-1/8 |
| Rotation Degree                              | 360               |
| Boom Adjustment Increments (in.)             | 12                |
| Cable Length (ft.)                           | 46                |
| Cable Diameter (in.)                         | 3/16              |
| DC (volts)                                   | 12                |
| Horsepower (HP)                              | 1                 |
| Mounting Plate Length (in.)                  | 12                |
| Mounting Plate Width (in.)                   | 12                |
| Capacity at 59-9/16" Fully Retracted (lbs.)  | 650               |
| Capacity at 59-9/16" Mid-Position (lbs.)     | 400               |
| Capacity at 59-9/16" Fully Extended (lbs.)   | 250               |
| Capacity at 74-1/4" Fully Retracted (lbs.)   | 1,000             |
| Capacity at 74-1/4" Mid-Position (lbs.)      | 770               |
| Capacity at 74-1/4" Fully Extended (lbs.)    | 600               |
| Capacity at 86-13/16" Fully Retracted (lbs.) | 1,250             |
| Capacity at 86-13/16" Mid-Position (lbs.)    | 950               |
| Capacity at 86-13/16" Fully Extended (lbs.)  | 780               |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=582>