

Steel Hitch Mounted Truck Jib Crane 47-1/2 In. Reach 600 Lb. Capacity Black

MODEL WTJ-HITCH

Overhead Lifting / Hitch-Mounted Truck Jib Crane

PRODUCT OVERVIEW

The hitch mounted Jib crane is ideal for on location operations, as well as, common secure transference of goods. The unit features a manual hand brake winch with cable and lifting hook for safe transporting. The welded steel construction with a powder coat black finish is durable and strong in the harshest of conditions. The offset design allows for full use of tailgate while winch is in operation. Unit is designed for vertical lifting only.

KEY FEATURES

- Hitch mounted jib crane is for on location operations and common secure transference of goods
- Includes a manual hand brake winch with cable and lifting hook for safe transporting
- Features durable construction for added strength and long life
- Offset design allows for full use of tailgate while winch is in operation

CORE PRODUCT DATA

ASSEMBLED WEIGHT
134 lbs

ASSEMBLED SIZE
19.8125" W x 44.5" L x 74.3125" H

SHIP WEIGHT
168 lbs

PACKAGE 1 SIZE
40" W x 48" D x 14" H

COLOR / FINISH
Black

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	600
Mounts to Receiver	Class III or Higher 2" Receiver
Boom Reach (in.)	47-1/2
Maximum Boom Height (in.)	80-11/16
Cable Length (ft.)	15
Cable Diameter (in.)	3/16
Hook Material	Zinc Plated Steel
Cable Material	Galvanized Steel
Hook Opening (in.)	7/8
Distance From Center to Center of Mounting Hole	2-3/4
Compliance	OSHA 29 CFR 1910.179
Standards	AWS D1.1/D1.6
Specifications	CMAA 74
ASME	NUM1
ANSI	B30.11
Overall Width (in.)	19-13/16
Overall Length (in.)	44-1/2
Overall Height (in.)	74-5/16

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=579>